

# System Accessories



## Fall Arrest Lanyard Extension Cable

Lanyard extension cables are used in fall arrest applications where the ceiling height makes access to the self-retracting lanyard impractical. The lanyard extension cable provides an extension of the overhead attachment point. This allows for easier access to the self-retracting lanyard. Common applications that face this problem include aircraft hangers and industrial facilities with high ceilings. Utilizing 1/4 inch wire rope with a zinc-plated O-ring and double action locking snaphook, the lanyard extension cable has a 5,000 lb. fall arrest load rating. Custom extension cable lengths are available upon request.

MODEL	LENGTH	WEIGHT	LINE
8-0166-10	10' (3.0m)	2.5 lbs. (1.1kg)	1/4" Galvanized Cable
8-0166-15	15' (4.6m)	3.5 lbs. (1.6kg)	1/4" Galvanized Cable
8-0166-20	20" (6.1m)	4.5 lbs. (2.0kg)	1/4" Galvanized Cable



Warning: Retrieval taglines should never be used as an anchorage.

## SRL Retrieval Tagline

Self-retracting lanyard retrieval taglines provide an easy way for workers to access the self-retracting lanyard snaphook for attachment to their harness D-ring. They also provide workers a way to completely retract the lifeline back into the SRL housing after use. This is an important safety step in discouraging workers from tying off SRLs fully extended while the lifeline is not in use. Each tagline consists of webbing and two stainless steel O-rings. Taglines can also be custom fit to any application length.

MODEL	LENGTH	WEIGHT	LINE
8-0173-20	20' (6.1m)	1.0 lbs. (0.5kg)	3/4" Polyester Webbing
8-0173-25	25' (7.6m)	1.2 lbs. (0.5kg)	3/4" Polyester Webbing
8-0173-30	30" (9.1m)	1.4 lbs. (0.6kg)	3/4" Polyester Webbing

Contact a Rigid Lifelines™ representative for more information and details!



[rigidlifelines.com](http://rigidlifelines.com)

(800) 869-2080 Toll Free  
(610) 286-0085 Fax  
(610) 286-7200 Local

Scan using your smart phone to watch product videos

## Carabiners

Rigid Lifelines™ carabiners are used to provide a locking connection between the fall arrest or fall restraint lanyard and the anchorage attachment point. Rigid Lifelines™ carabiners are manufactured from cold formed steel and each one is load tested to 3,600 lbs. (16kN). With a "twist to open" locking gate, they are easy to connect and lock in place. Our carabiners are certified to meet ANSI Z359.12-2009 and CSA Z259.12-01.

