



FS-FSP1230-G

Northstar Classic 30' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class

1

Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 37 in. (94 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 1 in. (2.2 m)

For full clearance requirements, see user instructions

MATERIAL SPECIFICATION

Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



Northstar Classic Cable SRL



Standards: ANSI Z359.14-2021
OSHA 1910.140, 1910.66 & 1926.502

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR														ATTACHMENT																
Part Number	Single Leg (S) / Dual Leg (D) SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook ①	ALU Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	LI Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	ALU Swivel Rebar Hook ⑧	Steel Captive Eye Carabiner ⑨	ALU Captive Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment ⑫	Trip Lock Steel Carabiner ⑬	ALU Carabiner ⑭	ALU Captive Eye Carabiner ⑮	ALU Snap Hook ⑯	Cab Mount Bracket ⑰	FS-EX313 ⑱	Soft Loop ⑲	Integrated BWB ⑳	1014 BWB ㉑	9012 BWB ㉒	9013 BWB ㉓	
FS-FSP1420-W	1	S	20	UHMPE Webbing	1X.05	Polymer	5.9	X												X										
FS-FSP1215-G	1	S	15	Steel Cable	ø3/16	Polymer	6.7		X											X										
FS-FSP1215-SS	1	S	15	S.S. Cable	ø3/16	Polymer	6.7		X											X										
FS-FSP1220-G	1	S	20	Steel Cable	ø3/16	Polymer	7.9		X											X										
FS-FSP1220-SS	1	S	20	S.S. Cable	ø3/16	Polymer	7.9		X											X										
FS-FSP1230-G	1	S	30	Steel Cable	ø3/16	Polymer	10.1		X											X										
FS-FSP1230-SS	1	S	30	S.S. Cable	ø3/16	Polymer	10.1		X											X										
FS-FSP1250-G	1	S	50	Steel Cable	ø3/16	Polymer	15.2		X											X										
FS-FSP1250-SS	1	S	50	S.S. Cable	ø3/16	Polymer	15.2		X											X										
FS-FSP1265-G	1	S	65	Steel Cable	ø3/16	Polymer	20.4		X											X										
FS-EX1080-G	1	S	80	Steel Cable	ø3/16	Polymer	27.4		X											X										
FS-EX10-100-G	1	S	100	Steel Cable	ø3/16	Polymer	30.4		X											X										

