



FS-FSP1250-G

Northstar Classic 50' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength polymer housing resists impact
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- All components are Z359.12 compliant



Class

1

Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 5 in. (2.3 m)

For full clearance requirements, see user instructions

MATERIAL SPECIFICATION

Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)



Northstar Classic Cable SRL



Standards: ANSI Z359.14-2021
OSHA 1910.140, 1910.66 & 1926.502

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR										ATTACHMENT											
Part Number	Single Leg (S) / Dual Leg (D) SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook	ALU Snap Hook	Dielectric Snap Hook	Steel Tie Back Hook	LI Steel Swivel Rebar Hook	Steel Swivel Rebar Hook	Steel Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook	ALU Swivel Rebar Hook
FS-FSP1420-W	1 S	20	UHMPE Webbing	1X.05	Polymer	5.9	X														
FS-FSP1215-G	1 S	15	Steel Cable	ø3/16	Polymer	6.7		X													
FS-FSP1215-SS	1 S	15	S.S. Cable	ø3/16	Polymer	6.7		X													
FS-FSP1220-G	1 S	20	Steel Cable	ø3/16	Polymer	7.9		X													
FS-FSP1220-SS	1 S	20	S.S. Cable	ø3/16	Polymer	7.9		X													
FS-FSP1230-G	1 S	30	Steel Cable	ø3/16	Polymer	10.1		X													
FS-FSP1230-SS	1 S	30	S.S. Cable	ø3/16	Polymer	10.1		X													
FS-FSP1250-G	1 S	50	Steel Cable	ø3/16	Polymer	15.2		X													
FS-FSP1250-SS	1 S	50	S.S. Cable	ø3/16	Polymer	15.2		X													
FS-FSP1265-G	1 S	65	Steel Cable	ø3/16	Polymer	20.4		X													
FS-EX1080-G	1 S	80	Steel Cable	ø3/16	Polymer	27.4		X													
FS-EX10-100-G	1 S	100	Steel Cable	ø3/16	Polymer	30.4		X													

